

TECHNICAL SPECIFICATIONS

Product type	LVT	Installation	Glue-downCut bevel
Overall thickness	2.5mm	Bevel	on 4 sides
Wear layer	0.55mm	Finish	Matte coating

CLASS OF USE

Domestic	23 Heavy	Commercial	33 Heavy
Light industrial	42 General		

WARRANTY

Domestic Warranty	Lifetime Limited	Commercial Warranty	15 Years Limited
-------------------	------------------	---------------------	------------------

CERTIFICATIONS

CE Marking	Certified
------------	-----------

CHEMICAL PROPERTIES

Norm	Item	Test method	Requirement	Result
EN 14041	Emissions	EN 717-1	$\leq 0.124 \text{ mg/m}^3$	Compliant
Decret No.2011-321	Emissions	ISO 16000	TVOC<1000µg/m3	Compliant
Prop 65	Orthophthalates	Spectrometry	ND	Compliant
CPSC & Prop 65	Ortho-Phthalates	CPSC-CH-C-1001-09.4	N.D.	Compliant
REACH	SVHC	Spectrometry, chromatography	$\leq 0.1\% \text{ (w/w)}$	Compliant

PHYSICAL PROPERTIES

Norm	Item	Test Method	Requirement	Result
ISO 10582	Dimensional stability	ISO 23999	$\Delta W/\Delta L \leq 0.25\%$	Compliant
	Curling	ISO 23999	$\leq 2\text{mm}$	Compliant
	Length tolerance	ISO 24342	$\leq 0.15\%$ of nominal L up to max 0.5mm	Compliant
	Width tolerance	ISO 24342	$\leq 0.1\%$ of nominal L up to max 0.5mm	Compliant
	Thickness tolerance	ISO 24346	+0.13mm/-0.1mm	Compliant
	Squareness	ISO 24342	$\leq 0.25\text{mm}/\leq 400\text{mm}$ $\leq 0.35\text{mm}/\geq 400\text{mm}$	Compliant
	Flatness	ISO 10582 Appendix B	Length: $\leq 0.50\%$ (concave) $\leq 1.0\%$ (convex) Width: $\leq 0.10\%$ (concave) $\leq 0.15\%$ (convex)	Compliant
	Wear layer thickness	ISO 24340	+13%/-10%	Compliant
	Openings between tiles/planks	ISO 10582 Appendix C	Aver 0.15mm / Max 0.2mm	Compliant
	Height difference between tiles/planks	ISO 10582 Appendix C	Aver 0.1mm / Max 0.15mm	Compliant
	Residual Indentation	ISO 24343-1	$\leq 0.1\text{mm}$	Compliant
	Castor chair	ISO 4918	Slight change only	Compliant
	Resistance to heat	ISO 105-B02:2014 Method 3A	$\geq \text{Grade 6}$	Compliant
		ASTM F1515	$\Delta E \leq 8$	Compliant
EN 16511	Impact resistance	EN 13329	$\geq 1600\text{mm}$	Compliant
	Martindale (Gloss retantion)	EN 16094	$\leq \text{MSR-A3}$	Compliant
	Martindale (Micro-scratch)	EN 16094	$\leq \text{MSR-B3}$	Compliant
	Furniture leg	EN 424	No visible change	Compliant
	Resistance to staining	EN 438-2	Group 1 and 2: Grade 5 Group 3: Grade 4	Compliant
EN 14041	Thermal resistance (R)	EN 12664/ASTM C518	NA	Compliant
	Slip resistance	EN 13893	≥ 0.3	Compliant
	Reaction to fire	EN 13501-1	Bfl-s1	Compliant
Others	Slip resistance	DIN 51130	$\geq \text{R9}$	Compliant

LEED SCORECARD

How our products fit into LEED v4:

Credit Type	Points	Criteria	Product Contribution
LEED BD+C and ID+C			
EQ Credit: Low-Emitting Materials	1-3 points	Option 1. Product has been tested according to California Department of Public Health (CDPH) Standard Method v1.2–2017 and complies with the VOC limits in Table 4-1 of the method. Additionally, the range of total VOCs after 14 days (336 hours) was measured as specified in the CDPH Standard Method v1.2 and is reported (TVOC ranges: 0.5 mg/m3 or less, between 0.5 and 5 mg/m3, or 5 mg/m3 or more).	CFL LVT products are GreenGuard Gold certified.
MR Credit: Building Product Disclosure and Optimization – Material Ingredients	1 point	Option 1. Material Ingredient Optimization International Alternative Compliance Path – REACH Optimization (value at 100% of cost or 1 product). End use products and materials have fully inventoried chemical ingredients to 100 ppm and assess each substance against the Authorization List – Annex XIV, the Restriction list – Annex XVII and the SVHC candidate list, (the version in effect June 2013,) proving that no such substance is included in the product. If the product contains no ingredients listed on the REACH Authorization, Restriction, and Candidate list.	CFL LVT products are REACH compliant.

WELL SCORECARD

The WELL Building Standard is founded on the understanding that facets of our environment interact with personal, genetic and behavioral factors to shape our overall health and well-being. By compiling leading practices in building design and management and referencing existing standards and best practice guidelines set by governmental and professional organizations, WELL works to harmonize and clarify existing thresholds and requirements.

Facet	Feature	Part	Requirements	Concept score	How our product contribute to obtain WELL level certification
AIR	01. Air quality standards	1. Standards For Volatile Substances	The following conditions are met: a. Formaldehyde levels less than 27ppb (0.027ppm) b. Total volatile organic compounds less than 500ug/m3 (0.5mg/m3)	PRECONDITION	a. Formaldehyde emission are less than 0.05mg/m3. b. The total volatile organic compounds are less than 0.5mg/m3.
	04. VOC Reduction	1. Interior Paints and Coatings	The VOC limits of newly applied paints and coating meet one of the following requirements: a. 100% of installed products meet California Air Resources Board (CARB) 2007, Suggested Control Measure (SCM) for Architectural Coatings, or South Coast Air Quality Management District (SCAQMD) Rule 1113, effective June 3, 2011 for VOC content. b. At minimum 90%, by volume, meet the California Department of Public Health (CDPH) Standard Method v1.1-2010 for VOC emissions	PRECONDITION	a. The VOC limits for California Air Resources Board (CARB) are less than 0.11ppm. b. Measured Concentration of Total Volatile Organic Compounds (TVOC): Less than/equal to 0.5 mg/m3 (in compliance with CDPH/EHLB Standard Method v1.1-2010). The product is GreenGuard Gold certified
		3. Flooring	The VOC emissions of all newly installed flooring must meet all limits set by the following, as applicable: a. California Department of Public Health (CDPH) Standard Method v1.1-2010.	PRECONDITION	Conforms to the CDPH/EHLB Standard Method v1.1-2010 (California Section 01350), effective January 1, 2012, for the school classroom and private office parameters when modeled as Flooring. The product is GreenGuard Gold certified
	11. Fundamental Material Safety	1. Asbestos and Lead Restriction	All newly-installed building materials meet the following materials composition requirements: a. No asbestos. b. Not more than 100 ppm (by weight) added lead.	PRECONDITION	a. No asbestos b. The product contain less than 100 ppm.
		2. Lead Abatement	For repair, renovation or painting on buildings constructed prior to any applicable laws banning or restricting lead paint, lead evaluation and abatement.	PRECONDITION	The product contain less than 90 ppm.
		3. Asbestos Abatement	To reduce hazards in buildings constructed prior to any applicable laws banning or restricting asbestos, the following testing, evaluation and abatement.	PRECONDITION	The product contain less than 90 ppm.
	25. Toxic Material Reduction	2. Flame Retardant Limitation	Halogenated flame retardants are limited in the following components to 0.01% (100 ppm) to the extent allowable by local code: a. Window and waterproofing membranes, door and window frames and siding. b. Flooring, ceiling tiles and wall coverings. c. Piping and electrical cables, conduits and junction boxes. d. Sound and thermal insulation. e. Upholstered furniture and furnishings, textiles and fabrics.	OPTIMIZATION	The product don't contain halogenated flame retardants
		3. Phthalate (Plasticizers) Limitation	DEHP, DBP, BBP, DINP, DIDP or DNOP (often found in polyvinyl chloride [PVC]) are limited in the following components to 0.01% (100 ppm): a. Flooring, including resilient and hard surface flooring and carpet. b. Wall coverings, window blinds and shades, shower curtains, furniture and upholstery. c. Plumbing pipes and moisture barriers.	OPTIMIZATION	In accordance with US Consumer Product Safety Improvement Act 2008 (CPSIA) (H.R.4040) Title I, Section 108 & California Proposition 65 & Annex XV II item 51&52 of the REACH Regulation (EC) No. 1907/2006 and amendment No. 552/2009, the product contains less than 100ppm.

5. Urea-Formaldehyde Restriction

Urea-formaldehyde presence is limited in the following components to 100 ppm:

- a. Furniture or any composite wood products.
- b. Laminating adhesives and resins.
- c. Thermal insulation.

OPTIMIZATION

The product contains urea-formaldehyde less than 100ppm.

END OF DOCUMENT